



An attractive square ceiling light available in two sizes and rated to IP65 for outdoor use. Frosted tempered glass lenses offer security and reduced glare.

- Die-cast aluminium base with extruded aluminium alloy body.
- Super white frosted tempered glass lens offering high visual comfort and even light distribution.
- UV protected pure polyester powder coated housing offering high corrosion resistance.
- High quality LED chips and driver.
- RAL9007, other RAL colours available on request.



Product Specification

CODE	OPTIC	LED Qty	CCT	LUMENS	CRI	POWER	IP	IK	WEIGHT
AVE-S12	40°	4	4000	1280	>70	12W	IP65	IK08	1.3
AVE-M23	40°	9	4000	2650	>70	23W	IP65	IK08	2.2


General Specification

Input voltage	100-240V
Input frequency	50/60Hz
Surge protection	0.5KV
LED Chips	CREE XTE
Lifetime	L70 >65,000hours L80 >65,000 hours L90 >65,000 hours
SDCM	SDCM<6
Class	Class I
Ambient temperature	-20°C to +50°C
Material	High pressure die-cast aluminium housing with tempered glass
Finish	Polyester powder coat cured under heat
RAL colour	RAL9007


Driver Details

Product	AVE-S12	AVE-M23
Driver	Eaglerise	
Dimming control	Non-Dimmable	
Driver current	700mA	700mA
Inrush current	30A MAX	20A MAX
Power factor	>0.9	>0.9

Dimensions



AVE-S



AVE-M