



A stylish wall lantern with an indirect light source to give a pleasant lighting effect, with a matching bollard range available. Ideal for residential and public recreation areas.

- Die-cast aluminium body and mounting plate.
- Highly transparent polycarbonate diffuser.
- Indirect light source offering high visual comfort and even light distribution.
- High quality LED chips and driver.
- UV protected pure polyester powder coated housing offering high corrosion resistance.
- Integrated switch to select colour temperature between 3000K and 4000K.
- RAL9005, other RAL colours available on request.



## Product Specification

CODE	OPTIC	LED Qty	CCT	LUMENS	CRI	POWER	IP	IK	WEIGHT
BRE-12	360°	56	3000/4000	1050/1080	>70	12W	IP65	IK09	1.6


## General Specification

Input voltage	100-240V
Input frequency	50/60Hz
Surge protection	0.5KV
LED Chips	2835
Lifetime	L70 42,000hours   L80 26,000 hours   L90 12,000 hours
SDCM	SDCM<6
Class	Class I
Ambient temperature	-20°C to +50°C
Material	High pressure die-cast aluminium housing with PC cover
Finish	Polyester powder coat cured under heat
RAL colour	RAL9005

**Driver Details**

<b>Product</b>	<b>BRE-12</b>
<b>Driver</b>	Eaglerise
<b>Dimming control</b>	/
<b>Driver current</b>	500mA
<b>Inrush current</b>	30A MAX
<b>Power factor</b>	>0.9

**Dimensions**



**BRE**