



A stylish round ceiling light available in three sizes and rated to IP65 for outdoor use. Tempered glass lenses offer security.

- Die-cast aluminium construction with fast installation design.
- Super white tempered glass lens and inbuilt reflector offering high visual comfort and even light distribution.
- UV protected pure polyester powder coated housing offering high corrosion resistance.
- High quality LED chips and driver.
- RAL9005, other RAL colours available on request.



Product Specification

CODE	OPTIC	LED Qty	CCT	LUMENS	CRI	POWER	IP	IK	WEIGHT
CAS-S9	80°	1	4000	770	>70	9W	IP65	IK08	0.9
CAS-M15	80°	1	4000	1450	>70	15W	IP65	IK08	1.4
CAS-L36	90°	1	4000	3730	>70	36W	IP65	IK08	2.2



General Specification

Input voltage	220-240V
Input frequency	50/60Hz
Surge protection	0.5KV
LED Chips	CREE COB, Philips 5050
Lifetime	L70 >36,000hours L80 >36,000 hours L90 36,000 hours
SDCM	SDCM<6
Class	Class I
Ambient temperature	-20°C to +50°C
Material	High pressure die-cast aluminium housing with tempered glass
Finish	Polyester powder coat cured under heat
RAL colour	RAL9005


Driver Details

Product	CAS-S9	CAS-M15	CAS-L36
Driver	Eaglerise		Galoppato
Dimming control	Non-Dimmable		Non-Dimmable
Driver current	350mA	350mA	900mA
Inrush current	15A MAX	30A MAX	≤7A, 10μs
Power factor	>0.8	>0.9	0.9


Dimensions



CAS-S



CAS-M



CAS-L