



A decorative and highly versatile ceiling light in die-cast aluminium with impact resistant polycarbonate diffuser. Ideal for canopies and courtyards.

- Die-cast aluminium construction.
- Impact resistant opal polycarbonate diffuser offering high visual comfort and even light distribution.
- UV protected pure polyester powder coated housing offering high corrosion resistance.
- High quality LED chips and driver.
- RAL9007, other RAL colours available on request.



## Product Specification

CODE	OPTIC	LED Qty	CCT	LUMENS	CRI	POWER	IP	IK	WEIGHT
CIL-25	100°	108	4000	2400	>70	25W	IP65	IK08	2.2


## General Specification

Input voltage	100-240V
Input frequency	50/60Hz
Surge protection	0.5KV
LED Chips	2835
Lifetime	L70 42,000hours   L80 26,000 hours   L90 12,000 hours
SDCM	SDCM<6
Class	Class I
Ambient temperature	-20°C to +50°C
Material	High pressure die-cast aluminium housing with PC
Finish	Polyester powder coat cured under heat
RAL colour	RAL9007

**Driver Details**

<b>Product</b>	<b>CIL-25</b>
<b>Driver</b>	Eaglerise
<b>Dimming control</b>	Non-Dimmable
<b>Driver current</b>	600mA
<b>Inrush current</b>	20A MAX
<b>Power factor</b>	>0.9

**Dimensions**



**CIL**