



Round and square projector floodlights suitable for a range of applications and installation methods. Two sizes in each style and a variety range of installation accessories available.

- Die-cast aluminium construction with tempered glass diffuser and two size options.
- Optical lenses offer visual comfort and uniform light distribution.
- High quality LED chips and driver.
- UV protected pure polyester powder coated housing offering high corrosion resistance.
- All external screws are in 304 stainless steel.
- RAL9007, other RAL colours available on request.



Optics

TP25



Product Specification

CODE	OPTIC	LED Qty	CCT	LUMENS	CRI	POWER	IP	IK	WEIGHT
FLO-S12	TP25	5	4000	1100	>70	12W	IP65	IK08	1.2
FLO-M23	TP25	9	4000	2150	>70	23W	IP65	IK08	2.0


General Specification

Input voltage	100-240V
Input frequency	50/60Hz
Surge protection	0.5KV
LED Chips	CREE XTE
Lifetime	L70 >60,500hours L80 >60,500 hours L90 >60,500 hours
SDCM	SDCM<6
Class	Class I
Ambient temperature	-20°C to +50°C
Material	High pressure die-cast aluminium housing with tempered glass
Finish	Polyester powder coat cured under heat
RAL colour	RAL9007


Driver Details

Product	FLO-S12	FLO-M23
Driver	Eaglerise	
Dimming control	No-dimmable	
Driver current	700mA	700mA
Inrush current	30A MAX	20A MAX
Power factor	>0.9	>0.9

Dimensions



FLO-S12



FLO-M23