



A modern and decorative bollard available in three heights and with an asymmetric light distribution offering very low upwards light. Taller versions also available for pedestrian areas.

- Aluminium die-cast lamp head and extruded aluminium body, available in three heights.
- High transparency polycarbonate diffuser.
- Asymmetric light source for optimum performance and reduced light pollution.
- High quality LED chips and driver.
- UV protected pure polyester powder coated housing offering high corrosion resistance.
- RAL9007, other RAL colours available on request.



Product Specification

CODE	OPTIC	LED Qty	CCT	LUMENS	CRI	POWER	IP	IK	WEIGHT
GAL-H60-15	130°	5	3000	1050	>70	15W	IP66	IK09	3.3
GAL-H80-15	130°	5	3000	1050	>70	15W	IP66	IK09	3.7
GAL-H100-15	130°	5	3000	1050	>70	15W	IP66	IK09	4.1

General Specification

Input voltage	100-240V
Input frequency	50/60Hz
Surge protection	0.5KV
LED Chips	Philips 5050
Lifetime	L70 100,000hours L80 70,000 hours L90 34,000 hours
SDCM	SDCM<6
Class	Class I
Ambient temperature	-20°C to +50°C
Material	High pressure die-cast aluminium housing with tempered glass
Finish	Polyester powder coat cured under heat
RAL colour	RAL9007

Driver Details

Product	GAL-H60-15	GAL-H80-15	GAL-H100-15
Driver	Eaglerise		
Dimming control	/		
Driver current	450mA	450mA	450mA
Inrush current	30A MAX	30A MAX	30A MAX
Power factor	>0.9	>0.9	>0.9

Dimensions



GAL