



High quality inground luminaire available in two sizes and suitable for a range of applications including uplighting of buildings and objects as well as generic open areas as walkover lights.

- 304 grade stainless steel housing and installation sleeve.
- Crystal clear 10mm tempered glass cover, the luminaire can withstand loads of 5000kg.
- Specially designed optics for optimum light distribution and low glare.
- Simple snap-in installation with hidden connections.
- Oil and water resistant with anti-slip glass.
- High quality LED chips, and DC 24V input for fixed output and DMX control options.
- All external screws are 304 stainless steel.




Product Specification

CODE	OPTIC	LED Qty	CCT	LUMENS	CRI	POWER	IP	IK	WEIGHT
HIB-9-L40	120°	49	4000	500	>70	9W	IP68	IK10	2.7
HIB-23-L100	120°	126	4000	1300	>70	23W	IP68	IK10	6.6

General Specification

Input voltage	24VDC
Input frequency	/
Surge protection	/
LED Chips	OSRAM 2835
Lifetime	L70 >36,000hours L80 >36,000 hours L90 30,000 hours
SDCM	SDCM<6
Class	Class III
Ambient temperature	-20°C to +50°C
Material	304 grade stainless steel housing with tempered glass
Finish	/
RAL colour	Stainless steel

Dimensions



HIB