



A minimalistic yet contemporary wall light that offers durability and comfort. Ideal for perimeter lighting and in walkways or stairwells.

- Die-cast aluminium body with prism tempered glass offering uniform light distribution.
- High quality LED chips and driver.
- High impact resistance and stainless steel anti-tamper screws.
- UV protected pure polyester powder coated housing offering high corrosion resistance.
- RAL9005, other RAL colours available on request.



Product Specification

CODE	OPTIC	LED Qty	CCT	LUMENS	CRI	POWER	IP	IK	WEIGHT
ISC-25	100°	132	4000	2150	>70	25W	IP65	IK08	3.9


General Specification

Input voltage	100-240V
Input frequency	50/60Hz
Surge protection	0.5KV
LED Chips	2835
Lifetime	L70 39,000hours L80 24,000 hours L90 11,000 hours
SDCM	SDCM<6
Class	Class I
Ambient temperature	-20°C to +50°C
Material	High pressure die-cast aluminium housing with tempered glass
Finish	Polyester powder coat cured under heat
RAL colour	RAL9005

Driver Details

Product	ISC-25
Driver	Eaglerise
Dimming control	Non-Dimmable
Driver current	600mA
Inrush current	20A MAX
Power factor	>0.9

Dimensions



ISC