



A high quality and impact resistant range of inground luminaires manufactured from stainless steel with specially designed optics for wall washing and uplighting applications.

- 304 grade stainless steel front and installation housing with pure aluminium body.
- Clear 10mm tempered glass which can withstand loads of 2000kg.
- Wall wash version with a tiltable light source and a general uplight option.
- Simple snap-in installation with hidden connections.
- Oil and water resistant with anti-slip glass.
- High quality LED chips, and DC 24V input.
- All external screws are 304 stainless steel.




Product Specification

CODE	OPTIC	LED Qty	CCT	LUMENS	CRI	POWER	IP	IK	WEIGHT
LEC-6A	30°×45° Tilt 15°	1	4000	140	>70	6W	IP68	IK10	0.88
LEC-6B	30°	1	4000	320	>70	6W	IP68	IK10	0.88
LEC-10	30°	1	4000	240	>70	10W	IP68	IK10	1.72


General Specification

Input voltage	24VDC
Input frequency	/
Surge protection	/
LED Chips	CREE XHP35.2
Lifetime	L70 >109,000hours L80 89,100 hours L90 41,900 hours
SDCM	SDCM<6
Class	Class III
Ambient temperature	-20°C to +50°C
Material	304 grade stainless steel front and pure aluminium with tempered glass
Finish	Surface oxidation
RAL colour	Stainless steel


Dimensions



LEC-6A



LEC-6B



LEC-10