



A stylish wall lantern with an indirect light source to give a pleasant lighting effect, with a matching bollard range available. Ideal for residential and public recreation areas.

- Die-cast aluminium body and mounting plate.
- Highly transparent polycarbonate diffuser.
- Indirect light source offering high visual comfort and even light distribution.
- High quality LED chips and driver.
- UV protected pure polyester powder coated housing offering high corrosion resistance.
- RAL9005, other RAL colours available on request.



Product Specification

CODE	OPTIC	LED Qty	CCT	LUMENS	CRI	POWER	IP	IK	WEIGHT
SAL-WL-12	160°	5	4000	1060	>70	12W	IP65	IK09	2.3


General Specification

Input voltage	100-240V
Input frequency	50/60Hz
Surge protection	0.5KV
LED Chips	Philips 5050
Lifetime	L70 100,000hours L80 70,000 hours L90 34,000 hours
SDCM	SDCM<6
Class	Class I
Ambient temperature	-20°C to +50°C
Material	High pressure die-cast aluminium housing with PC cover
Finish	Polyester powder coat cured under heat
RAL colour	RAL9005

Driver Details

Product	SAL-WL-12
Driver	Eaglerise
Dimming control	Non-Dimmable
Driver current	350mA
Inrush current	30A MAX
Power factor	>0.9

Dimensions



SAL