



50W



250W



500W



LED HIGH BAY

High efficiency Linear LED High Bay fittings are available with adjustable brackets and a choice of LED lenses, ranging from narrow beam, suitable for warehouse racking, to a wide beam suitable for open areas.

- . Emergency options available.
- . Various Beam angles.
- . Casambi controlled available.
- . Sensors available

Features

Light Source	LED SMD 3030
Input Voltage	AC 85V-265V
Body Material	Aluminium
CCT	5000K
Colour	Silver/Black
LED Driver	Meanwell or Tridonic
Certification	CE, SAA, UL
Warranty	5 Years
Working Lifetime	50,000 Hours

Option 1			
Part Number	Wattage	Lumen Output (lm)	Dimensions (LxWxH)
AL-LF/50W	50W	6,893lm	353mm x 115mm x 144mm
AL-LF/100W	100W	13,786lm	620mm x 115mm x 144mm
AL-LF/150W	150W	20,670lm	887mm x 115mm x 144mm
AL-LF/200W	200W	27,570lm	1154mm x 115mm x 144mm
AL-LF/250W	250W	34,460lm	1421mm x 115mm x 144mm
AL-LF/300W	300W	41,360lm	947mm x 230mm x 173mm
AL-LF/400W	400W	55,140lm	1214mm x 230mm x 173mm
AL-LF/500W	500W	68,932lm	1481mm x 230mm x 173mm
Option 2			
-30/70		30-70 Degree Beam Angle lens	
-60		60 Degree Beam Angle lens	
-60/120		60-120 Degree Beam Angle lens	
-90		90 Degree Beam Angle lens	